

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Engine Control and Alarm System

with type designation(s)

AHD 504 A, AHD 514 A, AHD 514 S, AHD 504 NG, AHD 504 OP, AHD 514 OP

Issued to

Böning Automationstechnologie GmbH & Co.KG
Ganderkesee, Niedersachsen, Germany

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Type	Temperature	Humidity	Vibration	EMC	Enclosure
AHD 504 A	B	B	A	B	*)
AHD 514 A	B	B	B	B	*)
AHD 514 S	B	B	B	B	*)
AHD 504 NG	B	B	B	B	*)
AHD 504 OP	B	B	A	B	*)
AHD 514 OP	B	B	B	B	*)

***) Required protection according to DNV GL Rules shall be provided upon installation on board**

Issued at **Hamburg** on **2018-07-10**

for **DNV GL**

This Certificate is valid until **2020-07-09**.

DNV GL local station: **Bremerhaven**

Approval Engineer: **Jens Dietrich**

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

AHD 504 A, Alarm System and Start-/Stop Unit:

9 x analog (selection 4–20mA / PT1000 / Bin via Jumper)
2 x analog (selection NiCrNi / 0-32V via Jumper)
3 x binary (Contact/Bedia with wire break monitoring)
6 x binary (control inputs)
1 x engine speed input (Pickup, galvanically isolated)
1 x Transistor 8A, wire break monitored, short-circuit proof (for solenoid or operating solenoid)
4 x relay 3A (32VDC, potential free)
1 x Transistor (32V/25mA)
2 x LED indicator (Power, Fault)
Interfaces: 2 CAN bus, RS232 diagnostic, serial for I/O extensions
Functions: Alarming, start-/stop Control, logging
Firmware-Version: 3.12.261
Degree of protection: IP20
Power supply: 24VDC

AHD 514 A, Alarm System and Start-/Stop Unit:

6 analog inputs 4..20mA
6 analog inputs PT100/PT1000
1 RPM input, galvanic isolated
2 add. binary inputs
6 binary inputs for control
2 voltage input for fuse trip and charging alternator
2 voltage input for speed-up/down
8 binary relay outputs 6A
2 binary transistor outputs (with wire break monitoring)
1 voltage output 1..5V/1..10V
2 status-LEDs
Interfaces: 2 CAN bus, RS232 diagnostic, serial for I/O extensions
Functions: Alarming, start-/stop Control, logging.
Firmware-Version: 3.12.283
Degree of protection: IP20
Power supply: 24VDC

AHD 514 S, Safety System

2 emergency stop inputs, direct acting, with wire break monitoring
5 binary inputs for automatic shut down with wire break monitoring
5 binary inputs for control (reset, override...)
1 RPM input, galvanic isolated
4 binary relay outputs, 6A
2 transistor outputs 8A, with wire break monitoring
1 transistor output 8A, short-circuit-proof with wire break monitoring
1 current output 4..20mA
2 status-LEDs
8 alarm-LED for override, emergency stop, overspeed and 5 other safety stop criteria
Interfaces: 1 CAN Bus for communication with AHD 514 A and AHD 514 OP, serial output
Functions: Manual emergency stops and automatic shut-down.
Firmware-Version: 1.19.22
Degree of protection: IP20
Power Supply 24VDC

AHD 504 NG, Grid and Generator Capture Unit:

3 x analog (400V AC, 50Hz / 60Hz) voltage and frequency measuring
Interfaces: 1 CAN Bus
Functions: measuring and monitoring of voltage and frequency of the power grid
Firmware-Version: 2.2.0.6
Degree of protection: IP20
Power Supply 24VDC

AHD 504 OP / AHD 514 OP, Operator Panels:

AHD 504 OP: 4.3" (16:9) colour display with automatic dimmed illumination
AHD 514 OP: 5.7" colour display with automatic dimmed illumination
Interfaces: CAN Bus for communication with AHD 504 A, AHD 504 NG, AHD 514 A and AHD 514 S.
Functions: Indication of most important analog engine parameters on each page,
engine status indication, alarm pages for acknowledged and unacknowledged alarms,
membrane keys for engine start/stop, buzzer stop, acknowledgement,
reset and page selection, buzzer
AHD 504 OP: Firmware-Version: 1.19
AHD 514 OP: Firmware-Version: 1.30.999.0
Degree of protection: IP20; front side: IP44
Power Supply 24VDC.

Additional Tests: Low temperature -25°C and -50°C non-operating performed successfully.

Application/Limitation

The system is suitable for auxiliary engines, emergency engines and multi engine propulsion systems. The Type Approval covers hardware and basic software listed under Product description. The installation instructions in the Operation Manual have to be observed.

The following documentation of the actual application is to be submitted for approval in each case:

- Reference to this Type Approval Certificate
- Specifications for Engine and/or reference to engine Type Approval Certificate
- System block diagram (showing independency between Safety System and Control and Monitoring System, including sensors separation)
- Power supply arrangement
- List of controlled and monitored points showing alarms and safety functions
- Software versions for particular delivery
- Test program for certification

Product certificate

Each delivery of the application system is to be certified according to Pt.4 Ch.9 Sec.1. The certification test is to be performed at the manufacturer of the application system, preferably at the engine/system application maker integrating control, monitoring and safety system, before the system is shipped to the yard. After the certification the clause for application software control will be put into force.

Clause for application software control

All changes in software are to be recorded as long as the system is in use on board. The records of all changes are to be forwarded to DNV GL for evaluation and approval. Major changes in the software are to be approved before being installed in the computer.

Type Approval documentation

AHD 514: Test reports : Zeiss P-QK/EMV 060/2009, Paconsult 09-2664, Paconsult 09-2665, EMV Services 09/9062-2-1; Performance test protocol 2009-12-21.
SW-Questionnaire RC3. AHD 504: Test reports : TÜV Nord No.12/12124-4, Paconsult 12-4220, Performance test prot. 2013-05-16.
AHD 504 / AHD 514 Operation Manual PaB-1271 V12, dated 2017-10-24.

Job Id: **262.1-029121-1**
Certificate No: **TAA00001XK**

Tests carried out

Applicable tests according to DNV GL Class Guideline CG-0339, November 2016.
Performance test, dated 2013-05-16.

Marking of product

Manufacturer, Type designation, serial number.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed at renewal of this certificate.

END OF CERTIFICATE