



TYPE APPROVAL CERTIFICATE

Certificate No:
TAA00002EE
Revision No:
1

This is to certify:

That the Level Transmitter

with type designation(s)
AHD-S 201

Issued to

Böning Automationstechnologie GmbH & Co.KG
Ganderkesee, Niedersachsen, Germany

is found to comply with

DNV rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Temperature	D
Humidity	B
Vibration	B
EMC	B
Enclosure	D

Issued at **Hamburg** on **2023-04-18**

This Certificate is valid until **2028-02-12**.

DNV local unit: **Magdeburg**

Approval Engineer: **Didier Girardin**

for **DNV**

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Hydrostatic probe with ceramic-capacitive sensor element.
Nominal pressure ranges: 0...0.04 up to 0...20bar
Power supply: 24V DC rated (10...32VDC)
Output signal: 4...20mA, 2-wire
Electrical connection: shielded cable with integrated air tube for atmospheric reference
Mechanical connection: Standard submersible probe, screw-in or flange version
Material housing: standard: stainless steel 1.4404 (316L), option: CuNi10Fe1Mn
Material seals: standard: FKM, option: EPDM, FFKM
Cable sheath: standard: TPE-E
Degree of protection: IP68
Optional: with PT100 temperature sensor (only with standard version), 3-wire.

Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval, by inclusion in an instrument list, by the manufacturer of the application system in each case. Reference is made to DNV Rules for Ships Pt.4 Ch.9 Control and Monitoring Systems

Type Approval documentation

Hidden

Tests carried out

Applicable tests according to class guideline DNV-CG-0339, August 2021

Marking of product

Manufacturer, model name AHD-S 201, serial number, pressure range and power supply.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE